

ACOUSTIS

Non Metallised

- Openness Factor . **Of** •
- Ultraviolet Transmittance . **Tuv** •
- Light Transmittance . **Tv** •
- Light Reflectance . **Rv** •
- Solar Transmittance . **Ts** •
- Solar Reflectance . **Rs** •
- Solar Absorption . **As** •
- G Value . **G tot** •



THIS FABRIC IS MADE FROM COATED FIBRE GLASS
ACOUSTIC ABSORPTION FACTOR a_w : 0.35 to 0.8

FENESTRATION PROPERTIES

	OF	Tuv	Tv	Rv	Ts	Rs	As	G Value	
								C Glaze	D Glaze
WHITE	1%	0%	17%	81%	18%	71%	11%	0.27	0.13
LINEN	1%	0%	15%	71%	17%	64%	19%	0.31	0.16
LIGHT GREY	1%	0%	9%	45%	12%	41%	47%	0.41	0.22
PEARL	1%	0%	6%	38%	9%	37%	54%	0.43	0.23
GREY	1%	0%	3%	27%	4%	24%	72%	0.48	0.26
CHARCOAL	1%	0%	0%	5%	0%	5%	95%	0.55	0.31

Data is current at time of printing. Please check website for most current information.



Absorption Factor

The acoustic absorption capacity of the material is expressed by its acoustic absorption factor a_w in the 3 octave bands: bass (below 200 Hz), medium (200 to 2000 Hz), treble (above 2000 Hz). **A high absorbing material will tend towards 1.**

Care Instructions

Clean with a sponge or soft brush dipped in soapy water. Leave roller shade down until completely dry.

Width

Maximum Roller Shade width: 2500 mm.

Fabric Warranty

5 Years (internal use only).

Railroad

This fabric can be railroaded.