
8

**REUSE PROTECT PRESERVE** 





## **PLANET**

MADE FROM 100% RECYCLED POLYESTER 100% PVC FREE RECYCLABLE

**ROLLER SHADE SOLAR CONTROL FABRIC** 

**NON METALLISED** 

Suitable for installation with:













## Non Metallised

Openness Factor . Of • Ultraviolet Transmittance . Tuv . Solar Transmittance . Ts . Solar Reflectance . Rs • Solar Absorption . As • G Value . G tot •



300 cm fabric width

0.38 mm thickness

THIS FABRIC IS MADE FROM 100 % RECYCLED POLYESTER

## **FENESTRATION PROPERTIES**

	OF	Tuv	Tv	Rv	Ts	Rs	As	G Va C Glaze	lue D Glaze
WHITE	5%	20%	49%	53%	48%	49%	4%	0.42	0.27
LINEN	5%	19%	43%	45%	45%	44%	11%	0.43	0.28
PEARL LINEN	5%	17%	35%	36%	42%	42%	16%	0.44	0.28
PEARL	5%	18%	32%	34%	40%	40%	19%	0.44	0.28
PEWTER	5%	12%	14%	11%	32%	29%	39%	0.47	0.28
BRONZE	5%	8%	10%	7%	29%	26%	46%	0.48	0.29
CHARCOAL	5%	6%	5%	8%	18%	25%	57%	0.49	0.29

Data is current at time of printing. Please check website for most current information.

## **Care Instructions**

Do not scrub. Do not use solvents or any abrasive substance that might damage the coating of the fabric. All types of chemicals will cause permanent damage to the fabric. Therefore, if cleaning windows etc., the blind will have to be raised to avoid any direct or indirect spray or splatter of chemicals on the fabric. Brushing softly and lightly with a clean, soft bristled brush will remove any loose dirt or dust. You can also use a vacuum with a soft brush. When vacuuming, avoid pulling or stretching the fabric.

**Fabric Warranty** 

Maximum Roller Shade width: 3000 mm. 5 Years (internal use only).

This fabric can be railroaded.











Order a memo sample: info@climatereadyfabrics.com.au