

SCREENATURE
Blackout

- Openness Factor . **Of** •
- Ultraviolet Transmittance . **Tuv** •
- Light Transmittance . **Tv** •
- Light Reflectance . **Rv** •
- Solar Transmittance . **Ts** •
- Solar Reflectance . **Rs** •
- Solar Absorption . **As** •
- G Value . **G tot** •

0%
openness factor

240 cm
fabric width

0.45 mm
thickness

425 g/m²
weight

THIS FABRIC IS MADE FROM 100 % FIBRE GLASS

FENESTRATION PROPERTIES

	OF	Tuv	Tv	Rv	Ts	Rs	As	G Value	
								C Glaze	D Glaze
WHITE	0%	0%	0%	83%	0%	70%	30%	0.26	0.12
OYSTER	0%	0%	0%	83%	0%	70%	30%	0.26	0.12
LINEN	0%	0%	0%	84%	0%	70%	30%	0.26	0.12
SAND	0%	0%	0%	84%	0%	70%	30%	0.26	0.12
SILVER GREY	0%	0%	0%	83%	0%	70%	30%	0.26	0.12
SABLE	0%	0%	0%	82%	0%	70%	30%	0.26	0.12
BRONZE	0%	0%	0%	81%	0%	70%	30%	0.26	0.12
BLACK	0%	0%	0%	86%	0%	70%	30%	0.26	0.12

Property values are derived from the white acrylic backing side that faces the window into the sun.
Data is current at time of printing. Please check website for most current information.



Care Instructions

Remove dust with vacuum cleaner or compressed air. Do not scrub. Use of solvents or abrasive substance will damage the coating of the fabric. All chemicals will cause permanent damage to the fabric. When cleaning windows raise the blind. Avoid any spray or splatter of chemicals on the fabric.

Width

Maximum Roller Shade width: 2400 mm.

Fabric Warranty

5 Years (internal use only).

Railroad

This fabric can **NOT** be railroaded.