

SCREENATURE  
Metallised

- Openness Factor . **Of** •
- Ultraviolet Transmittance . **Tuv** •
- Light Transmittance . **Tv** •
- Light Reflectance . **Rv** •
- Solar Transmittance . **Ts** •
- Solar Reflectance . **Rs** •
- Solar Absorption . **As** •
- G Value . **G tot** •




THIS FABRIC IS MADE FROM 100 % FIBRE GLASS

FENESTRATION PROPERTIES

	OF	Tuv	Tv	Rv	Ts	Rs	As	G Value	
								C Glaze	D Glaze
TITANIUM	4%	6%	7%	70%	7%	71%	22%	0.27	0.14
LIGHT GREY	4%	6%	6%	70%	6%	71%	23%	0.28	0.14
LINEN	4%	6%	6%	70%	7%	71%	22%	0.27	0.13
PEARL	4%	6%	6%	69%	6%	71%	23%	0.27	0.14
GREY	4%	6%	5%	69%	5%	71%	24%	0.27	0.14
BRONZE	4%	6%	5%	67%	5%	71%	24%	0.28	0.14
CHARCOAL	4%	6%	4%	66%	4%	70%	26%	0.28	0.14

Data is current at time of printing. Please check website for most current information.



Care Instructions

Handle fabric with care and wear clean gloves. Lightly dust regularly with clean feather duster. A hand-held vacuum with low suction may also be used. When vacuuming, avoid pulling or stretching the fabric. On metallised side, spot clean by gently blotting with a slightly damp cloth. Leave the blind down until completely dry.

Width

Maximum Roller Shade width: 2400 mm.

Fabric Warranty

5 Years (internal use only).

Railroad

This fabric can **NOT** be railroaded.