

SCREENATURE  
Non Metallised

- Openness Factor . **Of** •
- Ultraviolet Transmittance . **Tuv** •
- Light Transmittance . **Tv** •
- Light Reflectance . **Rv** •
- Solar Transmittance . **Ts** •
- Solar Reflectance . **Rs** •
- Solar Absorption . **As** •
- G Value . **G tot** •

**4%**  
openness factor

**240 cm**  
fabric width

**0.23 mm**  
thickness

**165 g/m<sup>2</sup>**  
weight

THIS FABRIC IS MADE FROM 100 % FIBRE GLASS

FENESTRATION PROPERTIES

	OF	Tuv	Tv	Rv	Ts	Rs	As	G Value	
								C Glaze	D Glaze
<b>WHITE</b>	4%	8%	33%	63%	33%	58%	9%	0.36	0.18
<b>LIGHT GREY</b>	4%	9%	27%	51%	29%	51%	20%	0.39	0.20
<b>LINEN</b>	4%	7%	30%	59%	30%	56%	14%	0.36	0.19
<b>SABLE</b>	4%	7%	22%	46%	25%	46%	29%	0.40	0.22
<b>PEARL</b>	4%	7%	13%	29%	18%	34%	48%	0.46	0.25
<b>GREY</b>	4%	5%	7%	12%	8%	14%	78%	0.53	0.29
<b>BRONZE</b>	4%	5%	6%	10%	7%	11%	82%	0.54	0.30
<b>CHARCOAL</b>	4%	5%	5%	6%	5%	6%	89%	0.55	0.31

Data is current at time of printing. Please check website for most current information.



**Care Instructions**

Use a plant-based eraser gently to remove superficial stains. Light dust regularly with a feather duster. A hand-held vacuum with low suction may also be used. When vacuuming, avoid pulling or stretching the fabric. Handle the fabric with care using clean gloves).

**Width**

Maximum Roller Shade width: 2400 mm.

**Fabric Warranty**

5 Years (internal use only).

**Railroad**

This fabric can **NOT** be railroaded.