
## SEA-TEX<sup>TM</sup>

## Metallised

Sea-Tex<sup>™</sup> is made with 50% recovered ocean bound plastic (approx. 125 grams per square meter) which equates to an average to large size commercial project using approximately 480kg of recovered ocean bound plastic. Available in five colours, 100% recyclable, fire retardant and PVC free.



Suitable for internal installation using:	Roller Panel Glide Vertical Shades Shades Shades	Internal installation only.				
Openness Factor:	3%					
Fabric Width:	280 cm					
Thickness:	0.45 mm					
Weight:	250 g/m²					
Composition:	50% post-consumer recycled content (recovered ocean bound plastic)					
	50% virgin polyester					
Fire Retardancy:	Compliant to AS1530.2 and AS1530.3.					

## **Fenestration Properties:**

	ć	1/3 <sup>3</sup>	4	67	19	85	Ps.	0 0 79,90	200 1000
SAND	3%	6%	8%	44%	8%	45%	47%	0.42	0.27
PEARL	3%	6%	8%	43%	8%	44%	48%	0.43	0.27
HAZE	3%	6%	8%	44%	8%	45%	47%	0.42	0.27
SILVER	3%	6%	9%	44%	9%	44%	47%	0.43	0.27
GRAPHITE	3%	4%	4%	42%	6%	44%	50%	0.43	0.27

G tot: Total solar factor, ratio of the energy transmitted through a window and solar protection device. Classification and reference glazing according to standard EN 14501

Data is current at time of printing. Please check website for most current information.

Openess Factor / OF
Ultraviolet Transmittance / Tuv
Light Transmittance / Tv
Light Reflectance / Rv
Solar Transmittance / Ts
Solar Reflectance / Rs
Solar Absorption / As
G Value / G tot

Certificates available on request.

**Environmental and Health Certification:** 



Cradle to Cradle Certified™ Bronze Certified.

A globally recognized measure of safer, more sustainable products



UL GREENGUARD ® Gold Certified

Guarantee of indoor air qualit (VOC)



Recycled Claim Standard (RCS)

A chain of custody standard to track recycled raw materials through the supply chain

Light-fastness:	5-6 (Blue Scale) Tested to ISO 105-B02:2014						
Sound Absorption:	Alpha-W = 0.30 sound absorption class: D (ISO354:2003 & ISO11654:1997)						
Care Instructions:	Handle fabric with care and wear clean gloves. Lightly dust regularly with clean feather duster. A hand-held vacuum with low suction may also be used. When vacuuming, avoid pulling or stretching the fabric. On metallised side, spot clean by gently blotting with a slightly damp cloth. Leave the blind down until completely dry.						
Warranty:	5 year warranty as complete roller shade systems for internal use. For more information regarding warranties and extended warranties, please contact Climate Ready Fabrics.						
Sustainability:	<ul> <li>50% post-consumer recycled content (recovered ocean plastic)</li> <li>100% recyclable</li> <li>PVC-free</li> </ul>						

## **Colour Range:**



Colours are to be used for reference purposes only. For an accurate colour sample, please contact Climate Ready Fabrics for a fabric swatch sample.

Specification information and other data are based on information available at the time of publication of this document and are subject to production tolerances and/or change without prior notice.



<sup>©</sup> Copyright January 2020 Climate Ready® Fabrics