



Climate Ready®  
Fabrics

A TEXTURED SCREEN FABRIC  
MADE WITH RECYCLED PET

# ReView

## Non Metallised

- 90% recycled PET / 10% virgin polyester
- UL Greenguard Gold Certified
- PVC Free
- Recyclable



Roller  
Shades



Panel Glide  
Shades



Vertical  
Shades

Suitable for internal installation only.

### Technical Data

<b>Openness Factor:</b>	4%
<b>Fabric Width:</b>	200 cm / 250 cm / 300 cm
<b>Thickness:</b>	0.5 mm
<b>Weight:</b>	275 g/m <sup>2</sup>
<b>Composition:</b>	90% recycled PET / 10% virgin polyester
<b>Fire Retardancy:</b>	Compliant to AS1530.2 and AS1530.3. <span style="float: right;">Certificates available on request.</span>

### Fenestration Properties

Design	OF (%)	As (%)	Rs (%)	Ts (%)	Tuv (%)	Tv (%)	Rv (%)	Gtot Value: A Glaze	Gtot Value: B Glaze	Gtot Value: C Glaze	Gtot Value: D Glaze
<b>White 001</b>	4	10	54	35	10	35	59	0,44	0,44	0,40	0,26
<b>Beige 002</b>	4	20	48	31	9	28	49	0,47	0,47	0,42	0,27
<b>Grey 003</b>	4	31	40	28	8	20	38	0,51	0,50	0,44	0,27
<b>Bronze 004</b>	4	84	8	7	6	6	4	0,67	0,65	0,54	0,30
<b>Black 005</b>	4	90	3	6	6	6	4	0,70	0,68	0,56	0,31

G tot: Total solar factor, ratio of the energy transmitted through a window and solar protection device. Classification and reference glazing according to standard EN 14501  
Data is current at time of printing. Please check website for most current information.

Openness Factor / <b>OF</b>
Ultraviolet Transmittance / <b>Tuv</b>
Light Transmittance / <b>Tv</b>
Light Reflectance / <b>Rv</b>
Solar Transmittance / <b>Ts</b>
Solar Reflectance / <b>Rs</b>
Solar Absorption / <b>As</b>
G Value / <b>G tot</b>

<b>Gtot refernece glazing types (EN 14501)</b>
<b>A:</b> Clear single glazing
<b>B:</b> Clear double glazing
<b>C:</b> Double glazing with coating
<b>D:</b> Reflective double glazing with coating

### Certification:



UL GREENGUARD®  
Gold Certified



OEKO-TEX  
Standard 100

**Light-fastness:** 6-7 (ISO 105 B02)

**Care Instructions:** Handle fabric with care and wear clean gloves. Lightly dust regularly with clean feather duster. A hand-held vacuum with low suction may also be used. When vacuuming, avoid pulling or stretching the fabric. Leave the blind down until completely dry.


**Warranty:** 5 year warranty as complete roller shade systems for internal use. For more information regarding warranties and extended warranties, please contact Climate Ready Fabrics.

**Sustainability:** ● Recycled PET ● PVC-free ● 100% recyclable


**Colour Range:**




**White 001**




**Beige 002**



**Grey 003**



**Bronze 004**



**Black 005**

Colours are to be used for reference purposes only.  
For an accurate colour sample, please contact Climate Ready Fabrics for a fabric swatch sample.